

**PIEFFE LAMITAKE 60 N**

CARATTERISTICHE <i>Properties</i>	UNITA' DI MISURA <i>Measurement unit</i>	NORMA <i>Test method</i>	VALORE <i>Value</i>
DENSITA' <i>Density</i>	g/cm ³	ISO 1183-1	1,41
TENSIONE DI ALL. A ROTTURA <i>Tensile strength at break</i>	N/mm ²	DIN 53455	67
ALLUNGAMENTO A ROTTURA <i>Elongation at break</i>	%	DIN 53455	35
MODULO DI ELASTICITA' <i>Modulus of elasticity</i>	N/mm ²	DIN 53457	3100
DUREZZA SHORE <i>Shore Hardness</i>	Shore D	DIN 53505	83
TEMPERATURA DI UTILIZZO IN CONTINUO <i>Working temperature range C</i>	°C	-	-50/+115
TEMPERATURA DI UTILIZZO TEMPORANEA <i>Working temperature range T</i>	°C	-	+140
AUTOESTINGUENZA <i>Fire behaviour</i>	-	UL 94	HB

All statements, technical information and recommendations contained in this database are presented in good faith, based upon tests believed to be reliable and practical field experience. The reader is cautioned, however, that PIEFFE srl cannot guarantee the accuracy or completeness of this information, and it is the customer's responsibility to determine the suitability of PIEFFE srl products in any given application.